




Model	SG720-2A	OG720-2A (ORv3)
Form Factor	7U 8GPU Universal Server with AMD Instinct™ Accelerators	7U 8GPU Universal Server with AMD Instinct™ Accelerators
		
Processor	Dual AMD EPYC™ 9005 Series Processors	Dual AMD EPYC™ 9005 Series Processors
TDP	Up to 500W	Up to 500W
Memory Type	Up to 6400 MT/s DDR5 RDIMM	Up to 6400 MT/s DDR5 RDIMM
DIMM Slot	24 DIMM Slots, Maximum: 6TB	24 DIMM Slots, Maximum: 6TB
GPU Support	AMD Instinct™ MI325X AMD Instinct™ MI350X	AMD Instinct™ MI325X AMD Instinct™ MI350X
Storage	Front 8 * 2.5" hot-swap NVMe U.2 Internal 2 * 2280 M.2 (PCIe Gen4)	Front 8 * 2.5" hot-swap NVMe U.2 Internal 2 * 2280 M.2 (PCIe Gen4)
PCIe Slot	Rear 4 * PCIe Gen5 x16 FHHL slots 4 * PCIe Gen5 x16 HHHL slots 1 * PCIe Gen5 x16 OCP 3.0 slot 1 * PCIe Gen5 x8 OCP 3.0 slot	Rear 4 * PCIe Gen5 x16 FHHL slots 4 * PCIe Gen5 x16 HHHL slots 1 * PCIe Gen5 x16 OCP 3.0 slot 1 * PCIe Gen5 x8 OCP 3.0 slot
Security	TPM 2.0 (optional)	TPM 2.0 (optional)
BMC	ASPEED AST2600 DC-SCM v1.0	ASPEED AST2600 DC-SCM v1.0
Power Supply	4000W 54V 3+3 Redundant, Titanium CRPS PSU 2000W 12V 1+1 Redundant, Titanium CRPS PSU	ORv3 Power Shelf
IO Ports	Rear 2 * USB 3.2 Gen1 ports 1 * 1GbE management port 1 * Mini-DP port 1 * Power button 1 * UID button Internal 1 * USB 3.2 Gen1 port	Rear 2 * USB 3.2 Gen1 ports 1 * 1GbE management port 1 * Mini-DP port 1 * Power button 1 * UID button Internal 1 * USB 3.2 Gen1 port
Dimension	447 mm (W) x 850 mm (D) x 306.1 mm (H) 17.60 in (W) x 33.47 in (D) x 12.05 in (H)	447 mm (W) x 850 mm (D) x 306.1 mm (H) 17.60 in (W) x 33.47 in (D) x 12.05 in (H)
More Info		